

2007 PUMPS, SANITATION

Rule Automatic Bilge Pumps



582305

582329

Rule Automatic Bilge Pumps

Designed for smaller boats. Automatic pumping without external floats or switches to tangle, stick or fail. Heavy duty construction. Completely submersible. Ignition protected. Rust and corrosion proof. Double insulated motor. Snap-off strainer for easy cleaning. Easy to install and offer maintenance free operation. Width 2-3/8". 12V DC.

582305 (25S)	500 GPH	Discharge 3/4"	Height 4"	\$70.95 F
582329 (27S)	1,100 GPH	Discharge 1-1/8"	Height 4-1/2"	\$106.95 F



582216



582222

Rule Automatic Bilge Pumps

Automatic pumping without external floats or switches to tangle, stick or fail. Heavy duty construction. Completely submersible. Double insulated motor. Rust and corrosion proof. Ignition protected. Snap-off strainer for easy cleaning. **582222** has an additional third wire, which can be connected to a switch for manual override or to an indicator light. Discharge 1-1/8". Height 7-3/4". Width 4-3/4". Sold each.

582575 (A53S)	1,800 GPH	110V AC	\$150.95 F
582216 (515-3)	1,500 GPH	12V DC	\$231.95 G
582222 (535-3)	2,000 GPH	12V DC	\$299.95 G

Rule-Mate™ Fully Automated Bilge Pumps

The pump and non-mercury float switch are in a single, compact housing. As the water level rises, so does the float switch, activating the pump when the water level reaches 2-1/8". There is no on/off cycling and therefore, no power use until the pump comes on. Exclusive Rule moisture tight seals. Easy clean snap-lock strainer bases. Silent and vibrationless operation. Anti-Airlock protection. Completely submersible. Stainless steel shafts. Ignition protection. No burn-out when run dry. Rust & corrosion protection. 12V DC. Height 4". Width 5". Sold each.

582343 (RM-500)	500 GPH	Discharge 3/4"	\$65.95 F
582355 (RM-750)	750 GPH	Discharge 3/4"	\$89.95 F
582367 (RM-1100)	1,100 GPH	Discharge 1-1/8"	\$116.95 F
582379 (RM-1500)	1,500 GPH	Discharge "	\$212.95 F
582381 (RM-2000)	2,000 GPH	Discharge "	\$273.95 F



Attwood Automatic Bilge Pumps

Attwood Sahara Series Automatic Bilge Pumps

Compact size and low profile design allow installation in tight places. High-efficiency, permanent magnet motor uses composite brushes and permanently lubricated bearings for longer life. The free flow of water around the motor housing keeps motor cool for extended life. 316 stainless steel motor shaft for saltwater corrosion resistance. Steel reinforced motor shaft seal ensures perfect alignment of shaft and seal, prevents leaks due to misalignment of motor shaft. Durable impeller is made of tough, high-impact, glass-filled polyester. Pump/Switch housing attaches to filter base with handy side-lock snaps for security and quick, one-hand removal for easy cleaning. Larger, more effective filter area resists clogging. Non-restrictive float movement avoids binding in on position or off position. Test knob allows for easy and immediate operational check without disassembly. Wiring is tinned and caulked for corrosion resistance and to eliminate wicking and water damage. New, molded three-wire seal is permanently fused to wire insulation to prevent leak paths. Reliable mechanical switch for long and dependable service. Contains no mercury. Length 5-1/2". Width 3-1/4". Height 4". 12 volts.

236186 (4505-7)	500 GPH	Hose Size 3/4" ID	\$53.95 H
236198 (4507-7)	750 GPH	Hose Size 3/4" ID	\$80.95 H
236201 (4511-7)	1,100 GPH	Hose Size 1-1/8" ID	\$97.95 H



PUMPS, SANITATION ²⁰⁰⁷

Mayfair Cartridge Bilge Pumps

mayfair
marine



Mayfair Automatic Cartridge Bilge Pumps

Salt water tough. Motor shaft is 316 stainless steel; housing is durable, noncorrosive ABS resin. Solid state electronic switch. No false starts. Pump on at 2-3/4" and off at 3/4". Non-clogging. Factory prewired for manual override. Cartridge or switch can be changed in minutes. Height 4-1/2". Diameter 3-3/8". 12V DC. Sold each.

470637 (05702) 750 GPH Discharge 3/4" **\$44.95 F**
470423 (06202) 1,250 GPH Discharge 1-1/8" **\$49.95 F**

mayfair
marine



Mayfair Automatic Cartridge Bilge Pump

Salt water tough. Motor shaft is 316 stainless steel; housing is durable, noncorrosive ABS resin. Solid state electronic switch. No false starts. Pump on at 2-3/4" and off at 3/4". Non-clogging. Factory prewired for manual override. Cartridge or switch can be changed in minutes. Height 4-1/2". Diameter 3-3/8". Discharge 3/4". 12V DC. Sold each.

470625 (05502) 500 GPH **\$35.95 F**

Lovett Automatic Bilge Pump

Lovett Pumps



Lovett Automatic Bilge Pump

High impact plastic housing, keeps electrical parts dry. Built-in switch gives dependable automatic action. Screen and intake slot areas are non-clogging under normal bilge conditions. UL Marine Department "Ignition Protected" rating. Capacity at 4 amp draw. Height 5-11/16". Width 8". Discharge 1-1/8". 12 volts.

450661 (1200-12V-AM) 1,193 GPH **\$185.00 F**
450748 (3201) Replacement Belt **\$5.79 F**

Marpac Electronic Bilge Switch



marpac

Marpac Electronic Bilge Switch

New SensaSwitch Ultra is not an old-fashioned "float switch"...because nothing floats. Water-sealed and solid-state. It simply eliminates all the parts that cause conventional switches to fail: NO moving parts to wear out. NO baffles or slots to clog. NO shafts or seals to leak. NO exposure to solvents or corrosion. And NO toxic Mercury to harm the environment. Up to 28.8 Volts DC at 20 amps. Rated at more than 480 watts, it can switch the biggest recreational pumps. Even handles multiple pumps!

7-2228

\$43.95 F 3Q